



### Performance level

- | API: GL-5
- | MT-1
- | SCANIA: STO 1.0
- | SAE: J2360
- | ZF TE-ML 02B, 05B, 07A, 08, 12B, 16F, 17B, 19C, 21B
- | MB 235.8
- | MACK GO-J
- | MAN 341Z2, 341 E3, 342 M3
- | IVECO AXLES
- | VOITH 3.325-340
- | MIL-L-2105E
- | ARVIN MARITOR O-76N
- | TMS-6816

### SYN GEAR 75W90

This gear oil is a semi-synthetic lubricating oil for mechanical transmissions, formulated with high quality special refined and synthetic base oils and special EP-additives to obtain the following properties:

- | excellent resistance against oxidation
- | a very high activity against wear, corrosion and foam
- | a low pour point
- | very good EP-properties
- | fuel economy



### Applications

This gear oil is used in hypoid differentials under very heavy duty conditions and should be used in all transmissions that require EP-transmission oils.

### Characteristics

	Unit	Average Value
Density at 15°C	kg/l	0.861
Viscosity 40°C	mm <sup>2</sup> /s	81.00
Viscosity 100°C	mm <sup>2</sup> /s	15.00
Brookfield viscosity at -40°C	mPas	130.000
Viscosity index		196
Flash point COC	°C	206
Pour point	°C	-45

### Packaging

