



Performance level

- API: GL-4
- API: GL-5
- API: MT-1
- DAF: GL5
- IVECO: VOITH 3.325-340
- MACK: GO-J EO-H
- MAN: 341 E-3
- MAN: 341 Z-2
- MAN: 342 M-3
- MAN: 3343-SL
- MAN: 342 S1
- MAN: 342 SL
- MB: 235.6/235.8
- MIL: PRF-2105E
- RENAULT: B0032/3 Annex 3
- SAE: J 2360
- SCANIA: STO 1
- ZF: TE-ML 02B
- ZF: TE-ML 05B
- ZF: TE-ML 07A
- ZF: TE-ML 08
- ZF: TE-ML 12B
- ZF: TE-ML 12L
- ZF: TE-ML 12N
- ZF: TE-ML 16F
- ZF: TE-ML 17B
- ZF: TE-ML 19C
- ZF: TE-ML 21B
- TMS 6816
- DIN 51517

UNI-GEAR S 75W90

This is a full synthetic lubricant based on carefully selected very high quality base oils, which can be used in a wide field of applications. Because of its special composition, it is particularly suited for synchronized gear boxes, as well as heavily loaded differentials.



Applications

This oil is recommended for all components of mechanical transmissions (gear boxes, transfer boxes, differentials, etc.) of trucks and four-wheel drive vehicles.

Characteristics

	Unit	Average Value
Density at 15°C	kg/l	0.869
Viscosity 40°C	mm ² /s	101.00
Viscosity 100°C	mm ² /s	15.40
Viscosity index		150
Flash point COC	°C	218
Pour point	°C	-40
Total base number	mgKOH/g	2.1

Packaging

