



## Transmax Agri Trans AS 80W

Anti-squawk transmission fluid

### Description

Castrol Transmax Agri Trans AS 80W is a universal, wet brake transmission/ hydraulic fluid designed to satisfy the various requirements of most tractor and farm machinery manufacturers. The AS (anti-squawk) characteristics of the formulation help to minimise the effect of wet brake chatter.

### Advantages

- Reduces/eliminates brake chatter
- Improves brake efficiency
- Prolongs equipment life
- Lowers maintenance costs

### Typical Characteristics

Name	Method	Units	Transmax Agri Trans AS 80W
Density @ 15C, Relative	ASTM D1298	g/ml	0.889
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	10.9
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	83.7
Viscosity Index	ASTM D2270	None	117
Viscosity, Brookfield @ -26C (80W)	ASTM D2983	mPa.s (cP)	31400
Pour Point	ASTM D97	°C	-33
Flash Point, COC	ASTM D92	°C	252

### Product Performance Claims

API GL-4

Meets - Ford ESN-M2C-86B, MFM1135

Can be used where NH 420A is specified.

Transmax Agri Trans AS 80W

01 Mar 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

[www.castrol.com/uk](http://www.castrol.com/uk)